




Nippel Type NP



NP - Ø1
Diameter

For samling af rør.


Fås også i rustfri udførelse: Type NR - Ø1

Ø1 nom	L	Li	Vægt
mm	mm	mm	kg
63	5	35	0,09
80	5	35	0,08
100	5	35	0,10
125	5	35	0,12
160	5	35	0,15
200	5	35	0,22
250	5	35	0,38

Ø1 nom	L	Li	Vægt
mm	mm	mm	kg
315	5	35	0,52
400	8	60	1,10
500	8	60	1,40
630	8	60	1,80
800	12	95	3,70
1000	12	95	5,20
1250	12	95	6,60



Muffe Type MF



MF - Ø1
Diameter

Anvendes til samling af fittings.


Fås også i rustfri udførelse: MR - Ø1

Ø1 nom	L	Lp	Vægt
mm	mm	mm	kg
63	-	40	0,06
80	12	40	0,08
100	12	40	0,10
125	12	40	0,12
160	12	40	0,15
200	12	40	0,22
250	12	60	0,38

Ø1 nom	L	Lp	Vægt
mm	mm	mm	kg
315	12	60	0,44
400	12	80	1,10
500	12	80	1,40
630	12	80	1,70
800	12	100	3,30
1000	12	100	4,60
1250	12	100	6,00



Skydenippel/Skydemuffe Type NPS/MFS




NPS - Ø1
Diameter

NPS er monteret med gummitætning i begge ender og uden stopvulst i den ene ende.
Anvendes f.eks mellem to afskårede kanaler.

Ø1 nom	Li	Vægt
mm	mm	kg
80	35	0,25
100	35	0,32
125	35	0,4
163	35	0,51
200	35	0,76
250	35	0,95

Ø1 nom	Li	Vægt
mm	mm	kg
315	35	1,2
400	60	1,8
500	60	2,2
630	60	2,8



MFS - Ø1
Diameter

MFS er monteret med gummitætning i den ene ende og muffemål i den anden.
For montering mellem fast rør og evt. T-stykke eller anden fitting med nippelmål.

Ø1 nom	Lp	Vægt
mm	mm	kg
80	35	0,25
100	35	0,32
125	35	0,40
160	35	0,51
200	35	0,76
250	35	0,95

Ø1 nom	Lp	Vægt
mm	mm	kg
315	35	1,20
400	60	1,80
500	60	2,20
630	60	2,80